





# CATV-ANALYZER

## ANALOG + DIGITAL



## VERY FAST WORK BY FULL AUTOMATIC!

- SIMULTANEOUS ANALYSIS IN BLOCKS OF 8 DIGITAL AND/OR ANALOG CHANNELS
- FULLY AUTOMATIC MEASUREMENTS – FAST QUALITY MEASUREMENTS
- WORLDWIDE TV-STANDARDS
- INGRESS MEASUREMENT
- LI-PO LONG BATTERY DURATION
- ROBUST METALHOUSING • RAIN PROOF BAG



### TECHNICAL DATA

#### MEASUREMENTS and SPECTRUM ANALYSIS

- **Frequency range:** 4–1000 MHz
- **Level meas. range:** 10–100 dB( $\mu$ V)/–50 to 60 dB(mV)  
120 dB( $\mu$ V) with ext. attenuator
- **Level accuracy:** 3 dB
- **Fast spectrum with MAX HOLD:** Full spect. capabilities with peak memory, variable span and automatic reference level.
- **Meas:** Digital and analog, BER, MER, constellation
- **Quality:** FAIL-MARGINAL-PASS
- **BARSCAN:** TV analog and digital bars scan form 10 to 100 channels
- **Data storage:** DATA-Logger

- **Memory plan:** World Wide countries with related channels plans are pre-memorized

#### GENERAL

- **Display:** Graphic monochrome LCD
- **Battery:** Rechargeable Li-Po battery pack, 5 hour duration
- **USB Micro:** For battery charge and PC interface for SW up-grade and memory plan management
- **Housing:** Metal housing, rain proof bag with shoulder strap
- **Dimensions:** H 95 mm × W 160 mm × D 34 mm (meter only)
- **Weight:** 0,5 kg